

S/N 09/135,413

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Leonard Forbes et al.

Serial No.: 09/135,413

Filed: August 14, 1998

Title: METHOD FOR OPERATING A DEAPROM HAVING AN AMORPHOUS
SILICON CARBIDE GATE INSULATOR



PATENT

Examiner: Viet Q. Nguyen

Group Art Unit: 2818

Docket: 303.354US2

#11/Amndt 0
Fored
10/22/99

AMENDMENT AND RESPONSE

Assistant Commissioner for Patents
Washington, D.C. 20231

10/18/99

In response to the Office Action mailed July 9, 1999, please amend the above identified patent application as follows:

IN THE CLAIMS

RECEIVED

Please amend the claims as follows:

OCT 22 1999

TECHNOLOGY CENTER 2800

15. (Amended) A method for operating a floating gate transistor comprising:
programming the floating gate transistor by inducing charge to migrate from a channel in a substrate through [a] an amorphous silicon carbide (a-SiC) gate insulator to a floating gate electrode in the floating gate transistor; and

erasing the floating gate transistor by inducing charge to migrate from the floating gate electrode through the amorphous silicon carbide (a-SiC) gate insulator to the channel.

16. (Amended) The method of claim 15 wherein:

programming comprises programming the floating gate transistor by inducing hot electron injection from a channel in a substrate through [an] the amorphous silicon carbide (a-SiC) gate insulator to a polysilicon floating gate electrode in the floating gate transistor; and

erasing comprises erasing the floating gate transistor by inducing charge to migrate from the polysilicon floating gate electrode through the amorphous silicon carbide (a-SiC) gate insulator to the channel through Fowler-Nordheim tunneling.

17. (Amended) A method for operating a floating gate transistor connected to a control line and a data line, the method comprising:

programming the floating gate transistor by providing a control voltage on the control

10/20/1999 00000105 09135413 11AM11 01 FC:102
02 FC:103
156.00 00
23.00